

HIGH QUALITY PRODUCTS

KASCO AIR CONDITIONING SERIES

MODEL:

- KF5-48RC
- KF5-48RHC
- KF10-96RC
- KF10-96RHC



MODEL:

- KW2-18RC
- KW2-24RC



MODEL:

- KS1-18RHC
- KS1-24RC
- KS2-12RC
- KS2-12RHC
- KS2-18RC
- KS2-24RC
- KS2-24RHC
- KS3-24RC
- KS3-24RHC



K A S C O

Products...forever!!!

PERFORMANCE	MODEL	WINDOW UNITS		DECORATIVE WALL MOUNTED SPLIT UNITS								CASSETTE		DUCTED		FREE STANDING UNITS				
		KW2 18RC	KW2 24RC	KS2 12RC	KS2 12RHC	KS2 18RC	KS1 18RHC	KS1 24RC	KS2 24RC	KS2 24RHC	KS3 24RC	KS3 24RHC	KC3 24RC	KC3 48RC	KD5 48RHC	KD8 60RHC	KF5 48RC	KF5 48RHC	KF10 96RC	KF10 96RHC
Cooling Capacity	W	18000	24000	12000	12000	18000	18000	24000	24000	24000	24000	24000	24000	48000	48000	60000	48000	48000	96000	96000
Heating Capacity	W	--	--	--	1460	--	2100	--	--	3450	--	3450	--	--	4850	5450	--	4850	--	7500
Power Supply	V,Hz	2 2 0 V - 2 3 0 V / 1 P H / 5 0 H z											3 8 0 V - 4 1 5 V / 3 P H / 5 0 H z							
Air Flow (Inside)	m ³ /h	850	850	500	500	860	860	860	1050	860	860	1150	1200	1750	1750	1750	1600	1600	4600	4600
Charge	Kg	1.4	1.4	.58	0.60	1.30	1.28	1.49	1.9	1.30	1.30	1.99	2.45	--	--	--	55	55	--	--
Rated Cooling Power Input	W	2400	2400	1200	1200	1880	1900	2380	2450	1880	1880	2850	2610	4700	4700	4700	2600	2600	--	--
Rated Cooling Current Input	A	11.0	11.0	5.5	5.5	8.8	8.7	11.0	8.8	8.8	8.8	13.8	11.9	8.3	8.3	8.3	8.3	8.3	10.7	10.7
Rated Heating Power Input	W	--	--	--	1100	--	1860	--	--	2500	--	2500	--	--	4400	4800	--	4400	--	6200
Rated Heating Current Input	A	--	--	--	5.1	--	8.6	--	--	12.0	--	12.0	--	--	8.1	8.8	--	8.1	--	12.4
Noise Level	DB (A)	62	62	38/52	38/52	46/57	46/57	50/60	46/57	46/57	46/57	51/61	60	64	64	64	55/64	55/64	63/88	63/88
Packing Dimensions	Inside	--	--	74.5X19.8X25.0	74.5X19.8X25.0	90X25.3X64.6	90X20.1X28.5	19.5X101.4X32	90X20.1X28.5	90X20.1X28.5	90X20.1X28.5	21.8X108X33	95X95X30.5	95X95X36.5	95X95X36.5	95X95X36.5	1820X540X370	1820X540X370	400X1200X1863	400X1200X1863
(DxWxH) mm	Outside	--	--	76.0X25.9X33.7	76.0X25.9X33.7	80X25.3X64.6	80X25.3X64.6	25.2X80X64.6	80X25.3X64.6	80X25.3X64.6	80X25.3X64.6	31X95X74.5	31X95X74.5	38X95X85.5	38X95X85.5	38X95X85.5	115X920X350	115X920X350	750X1450X964	750X1450X964
Net Dimensions	Inside	190X677X250	190X677X250	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
(DxWxH) mm	Outside	250X650X471	250X650X471	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--
Net Weight Kg	Inside	--	--	7.5	7.5	12	12	16	12	12	12	15	39	44	44	44	55	55	143	143
	Outside	78	78	30	30	52	52	52	52	52	52	78	68	99	99	99	130	130	148	148
Container Load	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

We reserve the right to change the specifications without prior notice.

Note: 1. Cooling capacities are based on 80°F DB/67°F WB (27°C DB/19.4°C WB) entering air at evaporator coil and 95°F DB (35°C DB) at condenser coil (ambient). The units are designed to work at ambient temperatures of 52°C.
2. Electric characteristics are based on 220-230V/1PH/50Hz / 380V-415V/3PH/50Hz.



Address: P.O. Box 41127, Dubai, U.A.E. * Tel.: +9714 2246223 * Fax: +9714 2246225
Email: info@kascohomeappliances.com

